75"

F50-SERIES F7550



Ultra-fast 20-point touch

Using the latest generation touch technology from FlatFrog, the F50 series delivers a highly superior writing experience that is incredibly fast and accurate. The display responds quickly to user interaction with up to 4 passive pens or up to 20 points of simultaneous touch.



2mm Optically bonded glass

Built with cutting-edge, protective glass with no parallax gap between the glass and the display, providing users with a pixel perfect touch experience.

pixel perfect touch experience. Enjoy the latest in 4K LCD technology that contributes to a lighter, thinner display that is incredibly energy efficient, while the anti-glare and anti-fingerprint glass ensure that content is always clearly visible.



Optimised for Windows 10 The F50 series comes with a built-in Windows swipe bar, optimised for Windows 10.



Latest Intel OPS slot

The OPS slot supports HDMI 2.0 allowing for 4K content to be run at 60Hz, while the Intel OPS (Open Pluggable Specification) allows for a module PC to be added easily to the display without cables.





Inductive key pad for control

Designed with ease of use in mind, the Advanced Connect and Control Bar features back-lit inductive key pads that complement the beautiful, sleek design of the F50 series.



Wireless Screen Sharing

The control bar also features a Wireless Screen Sharing button, enabling users to switch seamlessly to the dedicated HDMI input for 3rd party devices.



Integrated audio conferencing capability

A high-quality, front-facing soundbar module is included in the F50, ensuring that the display provides a crystal-clear audio experience, while the active microphone array allows the display to connect with a variety of Unified Communications based software, delivering the ultimate audio experience.

'OCOr



Pen aware functionality

The fine-tip stylus delivers extremely accurate writing and annotations on the display, while object recognition means that the display can easily distinguish between pen, finger and palm, delivering a smooth touch experience.

Guest IO 1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPS Audio 1 x 3,5mm audio out, 1 x 3,5mm audio in, 1 x optical (SPDIF) Control 1 x RS-232, 1 x LAN In Ethernet (RJ-45) PHYSICAL SPECIFICATIONS Product Dimensions Product Dimensions 1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inches Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Wall Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches IPC Mount 75 x 75 mm 2.95 x 2.95 inches IPC Mount 100 mm x 100 mm 3.93 x 3.93 inches OPS Slot Yes, 3840 x 2160 @ 60Hz Handles 4 OSD FUNCTIONS Sucre Auto Detect Function Yes Sucre Auto Detect Function Yes Sucre Auto Detect Function Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <30.0 W Standby <0.5 W ENVIRONMENTAL <0.5 W ENVIRONMENTAL <0.5 W ENVIRONMENTAL <0.5 C	DISPLAY	
Aspect Ratio 16-9 Assolution 340 x 210 00 40 4012 Assolution 640 x 210 00 4012 Bisponse Time 6 Bisponse Time 370 (cd/m2) Cantrast Ratio 4000-1 Assolution 178 * Bisponted Colours 30-bit Deep Colour Object Aston Landscape Orch System 1 Display Orientation Landscape Orch System 10 to 20 to cho points of Avocor inGlass" Intelligent fouch Supports 4 fine-lip pens Display Orientation 10 to 20 to cho points of Avocor inGlass" Intelligent fouch Supports 4 fine-lip pens Display Chartens Vindows 7 / 8 / 10 Mac OSX*: Linux* Orch System Vindows 7 / 8 / 10 Mac OSX*: Linux* Display Chartens 40 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Display Chartens 40 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Display Chartens 40 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Display Chartens 41 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Display Chartens 42 x 1584 hob 37 : 1 x 1584 hob Cot hob 100 Mod 1 x 158 Pan		75
Assolution 3940 x 2160 @ 60Hz designines 8 ms sesponso Time 8 ms sightness 370 (cd/m2) Contrast Ratio 4000:1 Viewing Angle 178' / 178' supported Colours 30-bit Deep Colour Display Orientation Landscape OUCH SYSTEM	Backlight	Direct-lit LED
Response Time8 msHighmess370 (cd/m2)Contrast Ratio400:1Alewing Angle178" / 178"Alewing Angle178" / 178"Supported Colours30-bit Deep ColourSilpely OttentationLandscapeOUCH SYSTEMImage Colour Dist of Avocor InGlass" Infelligent fouch Supports 4 fine-lip pensGuichUp to 20 touch points of Avocor InGlass" Infelligent fouch Supports 4 fine-lip pensGuichUp to 20 touch points of Avocor InGlass" Infelligent fouch Supports 4 fine-lip pensGuiss20 nm optically bonded, onti-liglere, onti-fingerpint glassUpported Operating SystemWindows 7 / 8 / 10: Mac OSX"; Linux"VUOOVes - 4 microphones - 5m reach20NECTIVIVVes - 4 microphones - 5m reach20NECTIVIVVes - 4 microphones - 5m reach20NECTIVIVVes - 4 microphone ArrayVes - 4 microphone XrayVes - 4 microphone XraySupport 1 x HSMA X 1 x XSMX SMA X 20 MohSupport 1 x HSMA X 1 x XSMX SMA X 20 MohSupport 2 x X SMA X 10	Aspect Ratio	16:9
sing https://dx370 (cd/m2)Contrast Ratio4000.1Alewing Angle78* / 178*Vipported Colours30-bit Deep ColourUpported Colours30-bit Deep ColourDeplay OtientationLandscapeOUCH SYSEM	Resolution	3840 x 2160 @ 60Hz
Sontrast Ratio 4000.1 Maxing Angle 178° / 178° Wayported Colours 30-bh Deep Colour Delplay Orientation Landscape OUCH SYSTEM Image: Colour System Interface 3 x USB 8 2.0, 1 x USB 8 3.0 Ouch Up to 20 touch points of Avocor InClass" Intelligent fouch. Supports 4 fine-tip pens Slass 2mm optically bonded, onti-glare, onti-fingerprint glass Supported Coperating System Windows 7 / 8 / 10: Mac OSX*; Linux' VIDO XUDO South To Speakers 40 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Vitcophone Array Yes - 4 microphones - 5m reach DONNECTURY X USBA APL AD 30°, 1 x USBA APL AD 30°, 1 x USBA APL AD 40°, 1 x USBA AP	Response Time	8 ms
Alewing Angle 178' / 178' Subpliced Colours 30-bit Deep Colour Display Orientation Landscape Orich System Interface 10 y 10 20 fouch points of Avocor InGlass'' Intelligent Touch Supports 4 fine-lip pens Siaks 2m optically bonded, onti-glane, onti-fingerprint glass siapported Operating System Windows 7 / 8 / 10: Mac OSX', Linux' VDIO Visite A fine-lip pens Siaki Supported Operating System Windows 7 / 8 / 10: Mac OSX', Linux' VDIO Visite A fine-dippone Array Visite A fine-dippone Array Yes - 4 microphones - 5m reach 20NECTIVIY Visite A fine-dippone Array Visite A fine Age Age Age Age Age Age Age Age Age Ag	Brightness	370 (cd/m2)
Supported Colours 30-bit Deep Colour Steplay Orientation Landscape OUCH SYSTEM Interface 10 uch System S x USB-B 2.0. 1 x USB-B 3.0 Force 3 x USB-B 2.0. 1 x USB-B 3.0 Force 2 x USB-B 2.0. 1 x USB-B 3.0 Force 3 x USB-B 2.0. 1 x USB-B 3.0 Force 3 x USB-B 2.0. 1 x USB-B 3.0 Force 3 x USB-B 2.0. 1 x USB-B 3.0 Force 3 x USB-B 2.0. 1 x USB-B 3.0 Force Windows 7 / 8 / 10: Mac OSX*; Linux* AUDO Substem Views 7 / 8 / 10: Mac OSX*; Linux* AUDO Substem Views 7 / 8 / 10: Mac OSX*; Linux* AUDO Substem Views 7 / 8 / 10: Mac OSX*; Linux* AUDO Substem Views 7 / 8 / 10: Mac OSX*; Linux* AUDI 2 x 1 SW Forward facing - Fach module: 4 x 32mm Drivers, 2 Passive Bittins peakers 4 0 [2 x 1 SW / 10: Mac OSX*; Linux* AUDI 2 x 1 SW Forward facing - Fach module: 4 x 32mm Drivers, 2 Passive Substep Converts Substep Colours Converts X HDM 2 x 1 x USB-A De 3 x 1 x USB-A 2 x 0 Hob, 1 x USB-A 2 x 0 FS Substep Converts Substep Converts x 4 x 1 x 0 FA 2 x 1 SW A 2 x 0 FS	Contrast Ratio	4000:1
Display OrientationLandscapeFOUCH SYSTEMInterface10 CH SYSTEM3 x USB-B 2.0, 1 x USB-B 3.0FouchUp to 20 touch points of Avocor InGlass" Intelligent touch Supports 4 fine-tip pensGlass2mm optically bonded, onti-glare, onti-fingerprint glassSupported Operating SystemWindows 7 / 8 / 10. Mac OSX*: Linx*ADDO3 x USB-B 2.0, 1 x USB-B 2.0, 1 x USB-B 2.0, 20 X*: Linx*Sult-In Speakers4 Ω 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 PassiveVilcrophone ArrayYe - 4 microphones - 5m reachCONNECTIVIV5 x HDMI 2.0, 1 x HDMI 2.0 for Declicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGAStandard IO3 x HDMI 2.0, 1 x HDMI 2.0 for Declicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGAGuest IO1 x HDMI 2.0, 1 x USB-B 1 ouch, 1 x USB-A 20 OPSAudio1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 82.322, 1 x LAN In Ethernet (RI-45)PHYSICAL SPECIFICATIONSProduct Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 112 loncesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 112 loncesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x 15.4 inchesPC Mount100 mm x 100 mm 3.49 x	√iewing Angle	178° / 178°
rouCH SYSTEMInterface3 x USB-B.2.0.1 x USB-B.3.0fouchUp to 20 touch points of Avocor InGlass" Intelligent touch Supports 4 fine-lip pensGlass2mm optically bonded, onti-glare, onti-fingerprint glassSupported Operating SystemWindows 7 / 8 / 10: Mac OSX*: Linux*AUDO3ult-in Speakers40 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 PassiveWilcorphone ArrayYes - 4 microphones - 5m reachCONNECTIVIV3 x HDMI 2.0, 1 x HDMI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hob 3.0**, 1 x USB-A CPS 3.0, 1 x HDMI Out, 1 x USB-A 20 OPSGuest IO1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 20 AUb, 1 x USB-A 20 OPSGuest IO1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 20 OPSAudio1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 8-532, 1 x LAN In Elhernet (R)-450PHYSICAL SPECIFICATIONS2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 1 32.2 Z Ibs / Gross: 73 kg 160.93 lbsNaid Mount (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount75 x 75 mm 2.95 x 2.95 inchesPC Mount900 mm x 100 mm 3.93 x 3.93 inchesPD Sol	Supported Colours	30-bit Deep Colour
netrace 3 x USB-B 2.0, 1 x USB-B 3.0 louch Up to 20 touch points of Avocar InGlass" Intelligent touch Supports 4 fine-tip pens Glass 2mm optically bonded, anti-fingerprint glass Supported Operating System Windows 7 / 8 / 10: Mac OSX"; Linux* AUDIO 2um optically bonded, anti-fingerprint glass Supported Operating System 4Q 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Wilcrophone Array Yes - 4 microphones - 5m reach CONNECTUTY 3x HDM1 2.0, 1 x HDM1 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA Suest IO 1 x HDM1 2.0, 1 x USB-A Too, 30, 1 x HDM1 CU, 1 x USB-A 20 OPS Audio 1 x S.3mm oudio out, 1 x 3.5mm audio in, 1 x optical (SPDIF) Control 1 x RS-232, 1 x LAN In Ethernet (RJ-45) Product Dimensions 1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inches Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 it6 x/3 s y 1 a 60.93 lbs Wold Mount (VESA) 800 mm x 400 mm 3.14.9 x 15.49 inches PC Mount 7 x 7 5mm 2.95 x 2.95 inches PC Mount 70 x x 75 mm 2.95 x 2.95 inches PC Mount 70 x x 75 mm 2.95 x 2.95 inches PC Mount	Display Orientation	Landscape
Touch Up to 20 touch points of Avocor inGlass" Intelligent touch Supports 4 fine-flip pens Glass 2mm optically bonded, cnil-glare, anti-fingerprint glass Supported Operating System Windows 7 / 8 / 10; Mac OSX*; Linux* ADIO	TOUCH SYSTEM	
Glass2mm optically bonded, anti-glare, anti-fingerprint glassSupported Operating SystemWindows 7 / 8 / 10: Mac OSX*; Linux*ADDOBulk Icrophone ArrayYes - 4 microphones - 5m reachCONNECTIVIYStandard IO $3 \times HDMI 2.0, 1 \times HDMI 2.0$ for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0*, 1 x USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO $3 \times HDMI 2.0, 1 \times HDMI 2.0$ for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0*, 1 x USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO $1 \times HDMI 2.0, 1 \times USB-B Touch, 1 x USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times NDS-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-A OPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-Serve AOPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-Serve AOPS 3.0. 1 x HDMI Out, 1 x USB-serve portGuest IO1 \times HDMI 2.0, 1 \times USB-Serve AOPS 3.0. 1 x HDMI Out, 1 x USB-serve portProvice ID1 \times R S - 22, 1 \times LAN In Ethernet (RJ - 45)Weight1 \times R S - 22, 1 \times LAN In Ethernet (RJ - 45)Provice IDProvice X = 139, 278 for Gross. 73 kg 16.093 lbsWeightNet: 60 kg 132 27 lbs / Gross. 73 kg 16.093 lbsPC Mount (VESA)800 mm x 400 mm 3.19 x 3.593 inchesPC Kount (VESA)800 mm x 400 mm 3.19 $	nterface	3 x USB-B 2.0, 1 x USB-B 3.0
Supported Operating System Windows 7 / 8 / 10: Mac OSX*; Linux* AUDIO AUDIO Sull-In Speakers 4Q 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive Wicrophone Array Yes - 4 microphones - 5m reach CONNECTIVITY Standard IO 3 x HDMI 20, 1 x HDMI 2, 0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB.A Hub 3.0**, 1 x USB.A 20 PbNI Out, 1 x USB arevice port Guest IO 1 x HDMI 20, 1 x HDMI 2, 0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB.A Hub 3.0**, 1 x USB.A 20 OPS Audio 1 x HS-232, 1 x LAN In Ethernet (R)-45) PHYSICAL SPECIFICATIONS Product Dimensions 1791.8 x 1114 9 x 103.1 mm 70.5 x 43.8 x 4.05 inches Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Mol Wall Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches PC PC Mount 75 x 75 mm 2.95 x 2.95 inches Source Auto Detect Function Yes Source Auto Detect Function Yes Saudo x 2.16 0 # 60Hz POWER Power Supply AC100-240V (Worldwide), 50/60Hz Power Supply AC100-2	iouch	Up to 20 touch points of Avocor InGlass [™] Intelligent touch Supports 4 fine-tip pens
ADDOBuilt-in Speakers $4\Omega \mid 2 x$ 15W forward facing - Each module: 4 x 32mm Drivers, 2 PassiveWilcrophone ArrayYes - 4 microphones - 5m reachCONNECTIVITYStandard IO $3 x$ HDMI 2.0, 1 x HDMI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0°°, 1x XUSB-A OPS 3.0, 1x HDMI Out, 1x USB-service portGuest IO1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPSAudio1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x Rs-232, 1 x LAN In Ethernet (RJ-45)PHYSICAL SPECIFICATIONSProduct Dimensions1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inchesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWall Mount (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesDPS SlotYes, 3840 x 2160 @ 60HzHandles4OSD FUNCTIONSSource Auto Detect FunctionYesmage Settings5 x User / Wird / Cinema / Game / SportsPOWERPOWEROver SuplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W	Glass	2mm optically bonded, anti-glare, anti-fingerprint glass
Built-In Speakers $4\Omega \mid 2 x$ 15W forward facing - Each module: 4 x 32mm Drivers, 2 PassiveMicrophone ArrayYes - 4 microphones - 5m reachCONNECTIVITYStandard IO3 x HDMI 2.0, 1 x HDMI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0**, 1x USB-A OPS 30, 1x HDMI Out, 1x USB service portGuest IO1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPSAudio1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 4.5.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 9.5.232, 1 x LAN In Ethernet (RJ-45)PHYSICAL SPECIFICATIONS1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inchesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWolf Mount (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesOPS SlotYes, 3840 x 2160 @ 60HzHandles4OSD FUNCTIONSSource Auto Detect FunctionYesImage Settings5 x User / Vivid / Cinema / Game / SportsPOWERPower SupplyAC 100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W	Supported Operating System	Windows 7 / 8 / 10; Mac OSX*; Linux*
Microphone ArrayYes - 4 microphones - 5m reachCONNECTIVITYStandard IO $3 \times$ HDMI 2.0, 1 x HDMI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGAGuest IO1 x HDMI 2.0, 1 x USB-A OPS 30.1 X HDMI OUT, 1 x USB service portGuest IO1 x HDMI 2.0, 1 x USB-A CPS 30.1 X HDMI OUT, 1 x USB-A 2.0 OPSAudio1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 8.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 8.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)Control1 x 8.232, 1 x LAN In Ethernet (R.45)PHYSICAL SPECIFICATIONSProduct DimensionsProduct Dimensions1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inchesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWoult (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesOPS SlotYes, 3840 x 2160 @ 60HzHandles4OSD FUNCIONSSource Auto Detect FunctionYesImage Settings5 x User / Vivid / Cinema / Game / SportsPower SupplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W	AUDIO	
CONNECTIVITY Standard IO 3 x HDWI 2.0, 1 x HDWI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0", 1 x USB-A OPS 3.0, 1 x HDMI Out, 1 x USB-A 2.0 OPS Guest IO 1 x HDMI 2.0, 1 x USB-B Fouch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPS Audio 1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF) Control 1 x RS-232, 1 x LAN In Ethernet (RJ-45) PHYSICAL SPECIFICATIONS 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Wall Mount (VESA) 800 mm x 400 mm 3.149 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches OSD FUNCTIONS 5 x User / Vivid / Clnema / Game / Sports Source Auto Detect Function Yes mage Settings 5 x User / Vivid / Clnema / Game / Sports POWER 20.5 W Power Supply AC100-240V (Worldwide), 50/60Hz Mainum Power Consumption 300 W Standby § 0.5 W POWER 20.5 W Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption 30.0 W </td <td>Built-in Speakers</td> <td>4Ω 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive</td>	Built-in Speakers	4Ω 2 x 15W forward facing - Each module: 4 x 32mm Drivers, 2 Passive
Standard IO $3 \times$ HDMI 2.0, 1 \times HDMI 2.0 for Dedicated Wireless Presentation Device, 1 \times DisplayPort 1.2a, 1 \times VGA 2 \times USB-A Hub 3.0", 1 \times USB-A OPS 3.0, 1 \times HDMI 0.1, 1 \times USB service portGuest IO1 \times HDMI 2.0, 1 \times USB-A DOPS 3.0, 1 \times HDMI 0.1, 1 \times USB-A 2.0 OPSAudio1 \times 3.5mm audio out, 1 \times 3.5mm audio in, 1 \times optical (SPDIF)Control1 \times RS-232, 1 \times LAN In Ethernet (RJ-45)PHYSICAL SPECIFICATIONS791.8 \times 1114.9 \times 103.1 mm 70.5 \times 43.8 \times 4.05 inchesProduct Dimensions1791.8 \times 1114.9 \times 103.1 mm 70.5 \times 43.8 \times 4.05 inchesShipping Dimensions2092 \times 1319 \times 286 mm 82.3 \times 51.9 \times 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWoll Mount (VESA)800 mm \times 400 mm 31.49 \times 15.49 inchesPC Mount75 \times 75 mm 2.95 \times 2.95 inchesPC Mount100 mm \times 100 mm 3.93 \times 3.93 inchesOPS FUNCTIONSSucce Auto Detect FunctionPower SupplyAC100-240V (Worldwide), 50/60HzPower SupplyAC100-240V (Worldwide), 50/60HzMainum Power Consumption<300 W	Vicrophone Array	Yes - 4 microphones - 5m reach
Guest IO 1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPS Audio 1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF) Control 1 x RS-232, 1 x LAN In Ethernet (RJ-45) PHYSICAL SPECIFICATIONS ************************************	CONNECTIVITY	
Audio 1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF) Control 1 x RS-232, 1 x LAN In Ethernet (RJ-45) Product Dimensions 1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inches Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Wall Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches DPS Slot Yes, 3840 x 2160 @ 60Hz 4andles 4 OSD FUNCTIONS 5 x User / Vivid / Cinema / Game / Sports POWer Source Auto Detect Function Yes Source Supply AC100-240V (Worldwide), 50/60Hz Waxinum Power Consumption <300 W	Standard IO	3 x HDMI 2.0, 1 x HDMI 2.0 for Dedicated Wireless Presentation Device, 1 x DisplayPort 1.2a, 1 x VGA 2 x USB-A Hub 3.0**, 1 x USB-A OPS 3.0, 1 x HDMI Out, 1 x USB service port
Control1 x RS-232, 1 x LAN In Ethernet (RJ-45)PHYSICAL SPECIFICATIONSProduct Dimensions1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inchesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWoll Mount (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount75 x 75 mm 2.95 x 2.95 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesPS SlotYes, 3840 x 2160 @ 60Hz4andles4OSD FUNCTIONSSource Auto Detect FunctionYesPower SupplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W	Guest IO	1 x HDMI 2.0, 1 x USB-B Touch, 1 x USB-A 2.0 Hub, 1 x USB-A 2.0 OPS
HYSICAL SPECIFICATIONSProduct Dimensions1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inchesShipping Dimensions2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inchesWeightNet: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbsWall Mount (VESA)800 mm x 400 mm 31.49 x 15.49 inchesPC Mount75 x 75 mm 2.95 x 2.95 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesPS SlotYes, 3840 x 2160 @ 60Hz4andles4OSD FUNCTIONSSource Auto Detect FunctionYesYesPOWEROver SupplyAC100-240V (Worldwide), 50/60HzAdammu Power Consumption<300 W	Audio	1 x 3.5mm audio out, 1 x 3.5mm audio in, 1 x optical (SPDIF)
Product Dimensions 1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inches Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Woll Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches PC Mount 4 DPS Slot Yes. 3840 x 2160 @ 60Hz Handles 4 DSD FUNCTIONS 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz Vaximum Power Consumption <300 W	Control	1 x RS-232, 1 x LAN In Ethernet (RJ-45)
Shipping Dimensions 2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Woll Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches PC Mount 4 DPS Slot Yes, 3840 x 2160 @ 60Hz tandles 4 DSD FUNCTIONS 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz vaximum Power Consumption <300 W	PHYSICAL SPECIFICATIONS	
Weight Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs Weight 800 mm x 400 mm 31.49 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches DPS Slot Yes, 3840 x 2160 @ 60Hz Handles 4 DSD FUNCTIONS Source Auto Detect Function Source Auto Detect Function Yes Source Auto Detect Function Yes POWER Source Auto Detect Function Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	Product Dimensions	1791.8 x 1114.9 x 103.1 mm 70.5 x 43.8 x 4.05 inches
Wall Mount (VESA) 800 mm x 400 mm 31.49 x 15.49 inches PC Mount 75 x 75 mm 2.95 x 2.95 inches PC Mount 100 mm x 100 mm 3.93 x 3.93 inches DPS Slot Yes, 3840 x 2160 @ 60Hz Handles 4 DSD FUNCTIONS Source Auto Detect Function Source Auto Detect Function Yes PC WER Vers/ 300 W Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	Shipping Dimensions	2092 x 1319 x 286 mm 82.3 x 51.9 x 11.2 inches
PC Mount75 x 75 mm 2.95 x 2.95 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesPC MountYes, 3840 x 2160 @ 60HzHandles4POS FUNCTIONSSource Auto Detect FunctionYesPower Supply5 x User / Vivid / Cinema / Game / SportsPOWERPower SupplyAC100-240V (Worldwide), 50/60HzMaintum Power Consumption<300 W	Veight	Net: 60 kg 132.27 lbs / Gross: 73 kg 160.93 lbs
PC Mount75 x 75 mm 2.95 x 2.95 inchesPC Mount100 mm x 100 mm 3.93 x 3.93 inchesPC MountYes, 3840 x 2160 @ 60HzHandles4POS FUNCTIONSSource Auto Detect FunctionYesPower Supply5 x User / Vivid / Cinema / Game / SportsPOWERPower SupplyAC100-240V (Worldwide), 50/60HzMaintum Power Consumption<300 W	Wall Mount (VESA)	800 mm x 400 mm 31.49 x 15.49 inches
PS Slot Yes, 3840 x 2160 @ 60Hz Handles 4 CDS FUNCTIONS Ves Source Auto Detect Function Yes mage Settings 5 x User / Vivid / Cinema / Game / Sports POWER 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	PC Mount	
DPS Slot Yes, 3840 x 2160 @ 60Hz Handles 4 DSD FUNCTIONS Source Auto Detect Function Yes mage Settings 5 x User / Vivid / Cinema / Game / Sports Power Supply 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	PC Mount	100 mm x 100 mm 3.93 x 3.93 inches
OSD FUNCTIONS Yes Source Auto Detect Function 5 x User / Vivid / Cinema / Game / Sports POWER 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	OPS Slot	Yes, 3840 x 2160 @ 60Hz
OSD FUNCTIONS Yes Source Auto Detect Function 5 x User / Vivid / Cinema / Game / Sports POWER 5 x User / Vivid / Cinema / Game / Sports Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W	Handles	
Source Auto Detect FunctionYesmage Settings5 x User / Vivid / Cinema / Game / SportsPOWERPower SupplyAC100-240V (Worldwide), 50/60HzPower SupplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W		
mage Settings5 x User / Vivid / Cinema / Game / SportsPOWERConver SupplyAC100-240V (Worldwide), 50/60HzPower SupplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 WStandby ≤ 0.5 WENVIRONMENTALDeperating Temperature0°C ~ 40°CStorage Temperature-20°C ~ 60°CHumidity20% ~ 85%		Yes
Power Supply AC100-240V (Worldwide), 50/60Hz Maximum Power Consumption <300 W		
Power SupplyAC100-240V (Worldwide), 50/60HzMaximum Power Consumption<300 W		
Maximum Power Consumption<300 WStandby \leq 0.5 WENVIRONMENTAL \circ C - 40°COperating Temperature \circ C - 40°CStorage Temperature-20°C - 60°CHumidity20% - 85%		AC100-240V (Worldwide), 50/60Hz
Standby ≦0.5 W ENVIRONMENTAL 0°C ~ 40°C Operating Temperature 0°C ~ 60°C Storage Temperature -20°C ~ 60°C Humidity 20% ~ 85%		
ENVIRONMENTAL Operating Temperature 0°C ~ 40°C Storage Temperature -20°C ~ 60°C Humidity 20% ~ 85%		
Operating Temperature0°C ~ 40°CStorage Temperature-20°C ~ 60°CHumidity20% ~ 85%		
Storage Temperature-20°C ~ 60°CHumidity20% ~ 85%		$0^{\circ}C \sim 40^{\circ}C$
Humidity 20% ~ 85%		
	SOFTWARE OPTIONS***	2070 0070

WHAT COMES IN THE BOX

1 x Remote control & batteries, 2 x 3mm fine-tip passive touch pen, 1 x UK, 1 x EU, 1 x US power cord, 1 x USB cable (3m | 118.1 inches), 1 x HDMI cable (3m | 118.1 inches), 1 x Quick Start Guide

WARRANTY

UK & Northern Ireland warranty: 3 year RTB warranty as standard with a 5 year on-site upgrade option available. EMEA & Republic of Ireland: 5 year RTB warranty as standard. ROW warranty: 3 year advanced replacement warranty as standard with a 4 or 5 year upgrade option available.





Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE. *Please note up to 20-point touch in PC mode with Windows 7/8/10, Mac OSX and Linux only supports single touch. **Touch input 1 only. ***Software options are included with every display purchase in EMEA only. +Preliminary specification, may be subject to change